

type VMK 32
VFK 32

08/2021



! Above stated body materials refer to the valve port connections that get in contact with the media only!

details needed for main valve

- orifice
- port
- function NC/NO
- operating pressure
- flow rate
- media
- media temperature
- ambient temperature
- type of actuation

details needed for pneumatic actuation

- nominal voltage
- type of protection
- actuation pressure range min/max
- pilot valve type

details needed for hydraulic actuation

- actuation pressure range min/max
- hydraulic control valve function

! The valves' technical design is based on media and application requirements. This can lead to deviations from the general specifications shown on the data sheet with regards to the design, sealing materials and characteristics.

! If order or application specifications are incomplete or imprecise there exists a risk of an incorrect technical design of the valve for the required application. As a consequence, the physical and / or chemical properties of the materials or seals used, may not be suitable for the intended application.

specifications not highlighted are standard
 specifications highlighted in grey are optional

2/2-way valve

pressure range
orifice
connection
function

design

body materials

valve seat

seal materials

ports

function
pressure range

Kv value
vacuum
pressure-vacuum

back pressure
media

abrasive media
damping

flow direction
switching cycles
switching time

media temperature
ambient temperature
flush ports
leak ports
limit switches
manual override
approvals
mounting
weight
additional equipment

nominal voltage

power consumption

protection
energized duty rating
connection
optional additional equipment
max. temperature

explosion proof


actuation pressure range
air consumption
cycle speed
control
pilot valve interface
actuator ports

actuation pressure range
control
actuator ports
by media


externally controlled

PN 0-100 bar
DN 32 mm
thread/flange

valve normally closed
symbol **NC**



valve normally open
symbol **NO**



pressure balanced, with spring return

- | | |
|------------------------|----------------------------|
| ① brass | ② steel galvanized |
| ③ brass, nickel plated | ⑤ without non-ferr. Metals |
| ④ steel, nickel plated | ⑥ stainless steel |

synthetic resin on metal

NBR PTFE, FPM, CR, EPDM

general specifications

VMK	threads G 1 1/4 - G 1 1/2	options	special threads
VFK	flanges PN 16 / 40 / 100		special flanges
	NC		NO

bar	0-16 / 0-40 / 0-64 / 0-100	
m ³ /h	20,0	
leak rate		< 10 ⁻⁶ mbar•L•s ⁻¹
P ₁ ⇌ P ₂		pressure side max. 100 bar
		vacuum side leak rate upon request
		available (max. 16 bar)
P ₂ > P ₁		
		gaseous - liquid - highly viscous -
		gelatinous - pasty - contaminated
		available

opening		
closing	by throttles on pilot valve	
A ⇌ B	as marked	bi-directional upon request
1/min	150	
ms	opening 100-3000	
	closing 100-3000	
°C	direct mounted pilot valve 60	remote mounted pilot valve outside
°C	direct mounted pilot valve 50	temperatur range of media max. 160 °C
		available
		available
		inductive / mechanical upon request
	via pilot valve	
		LR/GL/WAZ
		mounting brackets
kg	VMK 7,8 VFK 11,6	upon request

electrical specifications

U _n	DC 24 V	options	special voltage upon request
U _n	AC 230 V 50 Hz		special voltage upon request
DC	4,8 W		2,5 W [actuation pressure range 4-7 bar]
AC	pick up 11,0 VA holding 8,5 VA		
IP65 (P54)	acc. DIN 40050		
ED	100%		
	plug acc. DIN EN 175301-803 form B, 4 positions x90° / wire diameter 6-8 mm		
M12x1	connector acc. DESINA		connector acc. VDMA
	illuminated plug with varistor		
media	60°C		
ambient	50°C		
E Ex e II T5	nominal voltage U _n	DC 24 V	3,25 W
	power consumption	AC 230 V 50 Hz	2,90 W

pneumatic specifications

bar	4-10	options	
cm ³ /stroke	23		
	main valve speed variable by throttleson pilot valve		
	preferably 5/2 way pilot valve		
	co-ax / Namur	ISO 1	
2/4	G 1/8	G 1/4	



hydraulic specifications

bar	15-30 / 30-60	options	
	preferably 4/2 way control valve		
X/Y	G 1/4	NPT 1/4	

coax® data sheet - coaxial valve

type VMK 32
VFK 32



function: **NC**
closed when not energized



constructive length	L1	L2	L3
standard	269	201	325
with inductive limit switches	276	208	332
with force-feed lubrication nipple	306	238	362
with mechanical limit switches	304	236	360

flanges PN	DIN	ØD	Øk	Ød
16	EN 1092-1	140	100	18
40	EN 1092-1	140	100	18
100	EN 1092-1	155	110	22

function: **NO**
open when not energized



pneumatic specifications

